

UNITRONIC® FD Li2YCY (TP) A BA

Shielded, low-capacitance, twisted-pair PE/PVC data cable for power chain/cable carrier, UL AWM for USA+CAN


UNITRONIC® FD Li2YCY (TP) A B: Shielded, low-capacitance, twisted-pair PVC signal/data cable for power chain/cable carrier, UL AWM for USA and Canada

Info

Better priced than UNITRONIC® FD CP (TP) plus

Low capacitance, AWM by UL for USA+CAN

UNITRONIC® FD Li2YCY (TP) A BA: North-American Core Identification Colors



Mechanical and plant engineering



Suitable for outdoor use



Flame-retardant



Oil-resistant



Power chain



Interference signals



UV-resistant

Benefits

Improved transmission characteristics thanks to low-capacitance core insulation and twisted pairs

Cable specification optimized for use in power chain/cable carrier in the USA, on the basis of NFPA 79, Section 12.9.2

Last Update (25.05.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

UNITRONIC® FD Li2YCY (TP) A BA

Application range

Suitable for use in measuring, control and regulating circuits

Linear robots, automated handling equipment

Use in drag chain/cable carrier/power track - in case of horizontal installation travel distances up to 50 m

For use in chain/carrier: Please respect the assembly guidelines listed in Appendix T3

Product features

Low capacitance

EMC optimized thanks to overall copper braid shielding

Flexibility for use inside power chain/cable carrier

Oil-resistant according to DIN EN 50290-2-22 (TM54)

Flame-retardant acc. to IEC 60332-1-2,

UL VW-1, Cable Flame Test, CSA FT 1

Norm references / Approvals

Based on VDE 0812

UL AWM Style 2570 80°C 1000V (external interconnection) for USA (UL File No.: E63634) and in line with NFPA 79, Section 12.9.2

AWM I/II A/B 80°C 1000V acc. to CSA C22.2 No. 210-15 and certified by UL (cRU) for Canada

EU conformity and mark with regard to the European RoHS Directive

Product Make-up

Flexible conductor made of bare copper strands

Low-capacitance PE core insulation

Non-woven wrapping

Tinned-copper braiding

Outer sheath made of PVC

Outer sheath colour: black (similar to RAL 9005)

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000830

ETIM 5.0 Class-Description: Data cable

Core identification code:

UNITRONIC®

FD Li2YCY (TP) A BA:

- Pair 01: Black, Red;
- Pair 02: Black, White;
- Pair 03: Black, Green;
- Pair 04: Black, Blue;
- Pair 05: Black, Yellow;
- Pair 06: Black, Brown;
- Pair 07: Black, Orange;
- Pair 08: Red, White;
- Pair 09: Red, Green;
- Pair 10: Red, Blue;
- Pair 11: Red, Yellow;
- Pair 12: Red, Brown;
- Pair 13: Red, Orange;
- Pair 14: Green, White;
- Pair 15: Green, Blue;
- Pair 16: Green, Yellow;
- Pair 17: Green, Brown;
- Pair 18: Green, Orange;
- Pair 19: White, Blue;

Last Update (25.05.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

UNITRONIC® FD Li2YCY (TP) A BA

	<ul style="list-style-type: none"> - Pair 20: White, Yellow; - Pair 21: White, Brown; - Pair 22: White, Orange; - Pair 23: Blue, Yellow; - Pair 24: Blue, Brown; - Pair 25: Blue, Orange; - Exception Single-paired/24 - 22 AWG: Black, White
Mutual capacitance:	Up to 0.5 mm ² : 60 nF/km Up to 1.0 mm ² : 70 nF/km
Inductivity:	approx. 0.65 mH/km
Conductor stranding:	Fine wire From 0.5 mm ² : Finest wire/Conductor class 6 acc. to IEC 60228
Minimum bending radius:	Flexing: 7.5 x outer diameter Fixed installation: 4 x outer diameter
Loop resistance:	Ohmic (DC) and loop/bidirectional @ 20 °C 0.14 mm ² (26 AWG): 276.0 Ω/km; 0.25 mm ² (24 AWG): 158.0 Ω/km; 0.34 mm ² (22 AWG): 110.8 Ω/km; 0.5 mm ² (21 AWG): 78.0 Ω/km; 0.75 mm ² (19 AWG): 52.0 Ω/km; 1 mm ² (18 AWG): 39.0 Ω/km
Temperature range:	Flexing: VDE: -5 °C to 70 °C UL AWM: -5 °C to 80 °C Stationary use: VDE: -40 °C to 70 °C UL AWM: -5 °C to 80 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

UNITRONIC® FD Li2YCY (TP) A BA

Article number	Number of pairs and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
0031427	1 x 2 x 0.14	4.3	11.2	23
0031428	2 x 2 x 0.14	5.9	19.4	42
0031429	3 x 2 x 0.14	6.2	23.4	47
0031430	4 x 2 x 0.14	6.7	27.1	57
0031431	5 x 2 x 0.14	7.3	37.4	68
0031432	6 x 2 x 0.14	7.5	49.4	86
0031433	8 x 2 x 0.14	8.8	54.8	109
0031434	10 x 2 x 0.14	10.1	60.1	120
0031435	12 x 2 x 0.14	9.8	61.6	150
0031436	1 x 2 x 0.25	4.7	14.9	27
0031437	2 x 2 x 0.25	6.6	32	57
0031438	3 x 2 x 0.25	7	38.4	72
0031439	4 x 2 x 0.25	7.6	43.2	85
0031440	5 x 2 x 0.25	8.5	51.5	92
0031441	6 x 2 x 0.25	8.8	71.8	114
0031442	8 x 2 x 0.25	10.3	74.4	145
0031443	10 x 2 x 0.25	11.8	90	182
0031444	14 x 2 x 0.25	12	111.2	213
0031445	25 x 2 x 0.25	16.3	310	310
0031446	1 x 2 x 0.34	5.1	18.1	36
0031447	2 x 2 x 0.34	7.3	41	69
0031448	3 x 2 x 0.34	8	52	93
0031449	4 x 2 x 0.34	8.7	59	106
0031450	5 x 2 x 0.34	9.7	67	136
0031451	6 x 2 x 0.34	10	86.2	165
0031452	8 x 2 x 0.34	11.8	107.5	221
0031453	10 x 2 x 0.34	13.7	131.1	274
0031454	1 x 2 x 0.5	5.5	23	47
0031455	2 x 2 x 0.5	8.3	50	99
0031456	3 x 2 x 0.5	8.8	71.8	120
0031457	4 x 2 x 0.5	9.8	74.4	130
0031458	5 x 2 x 0.5	10.7	84.5	164
0031459	6 x 2 x 0.5	11.3	99.6	182
0031460	8 x 2 x 0.5	13.2	144.3	278

Last Update (25.05.2023)

©2023 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

UNITRONIC® FD Li2YCY (TP) A BA

Article number	Number of pairs and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
0031461	10 x 2 x 0.5	15.2	176	325
0031462	14 x 2 x 0.5	15.5	215.4	401
0031463	1 x 2 x 0.75	5.9	35	61
0031464	2 x 2 x 0.75	9	60	104
0031465	3 x 2 x 0.75	9.8	85.7	148
0031466	4 x 2 x 0.75	10.7	93.6	167
0031467	5 x 2 x 0.75	11.9	115	202
0031468	6 x 2 x 0.75	12.3	130.4	233
0031469	8 x 2 x 0.75	14.7	192.2	330
0031470	10 x 2 x 0.75	16.7	258	390
0031471	14 x 2 x 0.75	17	316.6	515
0031472	1 x 2 x 1.0	6.3	42	71
0031473	2 x 2 x 1.0	9.9	73	126
0031474	3 x 2 x 1.0	10.5	93.6	167
0031475	4 x 2 x 1.0	11.8	117.8	213
0031476	5 x 2 x 1.0	13.1	139	247

Last Update (25.05.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16