

## EPIC® DATA PB M12/M12

PROFIBUS M12 control cabinet feed-through, shielded

sensor/actuator control cabinet feed through with bipolar/screw mounting (B-coded)



Supplementary automation components from Lapp



Mechanical and plant engineering



Interference signals



Waterproof

### Benefits

M12 connector on both sides

Plug & Play for flexible connection solutions

### Application range

Mechanical and plant engineering

### Product features

For PROFIBUS applications

Bipolar/screw mounting

### Product Make-up

5-pin control cabinet feed-through, M12 B-coded

M12 plug on M12 socket

Screened version

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC002061

Last Update (11.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## EPIC® DATA PB M12/M12

Classification ETIM 6:	ETIM 5.0 Class-Description: Sensor-actuator connector chassis ETIM 6.0 Class-ID: EC002061 ETIM 6.0 Class-Description: Sensor-actuator connector chassis
Material:	Contact: CuZn Contact surface: Au (gold) Contact carrier: PA 66 Knurl: Nickel-plated brass Sealing: FKM
Protection rating:	IP 67
Ambient temperature (operation):	Plug/socket -25°C to +85°C
Coding:	B - inverse (PROFIBUS)
Rated current (A):	4 A

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

**EPIC® DATA PB M12/M12**

Article number	Article designation	Number of pins	Rated voltage (V)	PU
Control cabinet feed through				
22262021	AB-C5-DSI-M12MSB-M12FSB-M16-SH	5	60	1

Last Update (1.1.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16