

UNITRONIC® BUS PB HEAT 180

PROFIBUS cable with an extended temperature range up to +180°C

Bus cable for PROFIBUS-DP, -FMS and FIP. No need for additional cable protection against high temperatures. Oil resistance. Temp. range from -50 bis +180°C

 Verticate and plant engineering

 Vireistant

 Vireistant

Product features

For use in high temperature areas with up to 180 °C

High oil-resistance

Product Make-up Solid and bare copper conductor Wire insulation Fluorethylen

Last Update (11.12.2022) ©2022 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02_03.16



PRODUCT INFORMATION

UNITRONIC® BUS PB HEAT 180

Overall screening with copper braid and plastic-laminated aluminium foil Outer sheath: FEP, violet (RAL 4001)

Technical Data	
Classification ETIM 5:	ETIM 5.0 Class-ID: EC000830 ETIM 5.0 Class-Description: Data cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000830 ETIM 6.0 Class-Description: Data cable
Mutual capacitance:	approx. 28 nF / km
Peak operating voltage:	(not for power applications) 250 V
Minimum bending radius:	Repeated: 7 x Outer Diameter Single: 5 x Outer Diameter
Test voltage:	3600 V DC (3 sec.)
Characteristic impedance:	(3 - 20 MHz): 150 ± 15 Ohm
Temperature range:	-50 to +180°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil \leq 30 kg or \leq 250 m, otherwise drum

SIMATIC® is a registered trademark of SIEMENS AG. FIP is a registered trademark of World FIP

Lapp Kabel is a member of the PROFIBUS user organisation (PNO)

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article designation	Number of pairs and conductor diameter (mm)	Copper index (kg/km)	Weight (kg/km)
3031981	UNITRONIC® BUS PB HEAT 180	1 x 2 x 0,64	21.7	64.1
3031981	UNITRONIC® BUS PB HEAT 180	1 x 2 x 0,64	21.7	64.1

O LAPP