

# **EPIC® DATA CAN TR M12**

M12 Terminating resistor for DeviceNet/CANopen

Extremely robust M12 bus termination (resistor) for individuell use within field bus networks (PROFIBUS, DeviceNet and CANopen).

### Info

Fully suitable for industrial use









Supplementary automation components from Lapp



Assembly time



Space requirement

### **Benefits**

Cost efficient termination of a bus systems Space-saving due to compact dimensions. Robust design

### Application range

Mechanical and plant engineering

## **Product features**

120  $\Omega$  terminating resistor for DeviceNet/CANopen

### **Product Make-up**

Straight connector M12 with integrated termination resistor

### **Technical Data**

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000448

Last Update (11.12.2022) ©2022 Lapp Group - Technical changes reserved Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16





# **EPIC® DATA CAN TR M12**

ETIM 5.0 Class-Description: Terminal resistor

Classification ETIM 6: ETIM 6.0 Class-ID: EC000448

ETIM 6.0 Class-Description: Terminal resistor

Protection rating: IP65/IP67

Ambient temperature (operation): -25°C to +90°C

Contact material: CuSn

Coding: A - Standard (CANopen/DeviceNet)

Rated current (A): 4 A

### Note

DeviceNet is a registered trademark of ODVA

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



# **EPIC® DATA CAN TR M12**

### PU Article designation Number of pins Rated voltage (V) Article number Plug, unshielded (terminating resistor) AB-C5-M12MS-DN-TR 5 60 5 22260766