


## PRODUCT INFORMATION

## **Distribution Box M8**

Distribution box with M8 slots and master cable/connection M12/M16

Passive distribution boxes with M8 slots and fixed installed master cable in a fully sealed housing for a structured wiring of sensors and actuators





# :**R**U<sub>11</sub>



Supplementary automation components from Lapp



Mechanical and plant engineering



Space requirement



Power chain



#### Benefits

Cost efficient and rational wiring of sensors and actuators Instead of numerous individual conductors, one master cable is laid to the control unit Hybrid cable for signal and power transmission There are no assembly costs as the master cable is already pre-assembled Suitable for drag chains

#### **Product features**

Single-occupied boxes With fixed master cable or M12/M16 socket LEDs indicate the operating mode of the distributor and the status of the sensors PWIS-free

Last Update (13.12.2022) ©2022 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02\_03.16



### **Distribution Box M8**

Norm references / Approvals

E-File number: E75770

#### **Product Make-up**

Core insulation: PVC Outer sheath: PUR, black

### **Technical Data**

Classification ETIM 5:

Classification ETIM 6:

Protection rating:

Ambient temperature (operation):

ETIM 5.0 Class-ID: EC002585 ETIM 5.0 Class-Description: Passive sensor-actuator interface ETIM 6.0 Class-ID: EC002585 ETIM 6.0 Class-Description: Passive sensor-actuator interface

IP65/IP67 -30°C to +80°C

Fixed installation -40°C to +90°C Flexing -5°C to 80°C

Current rating per slot:

#### Note

Copper price basis: inclusive of copper. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

2 A

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Unoccupied slots must be covered with protective caps - ArtNo. 22260606 (M8); 22260605 (M12).

Article number 22260028 22260029 22260030 22260031 22260032	Article designation	Connection cable (No. of poles)	Length (m)	Number of slots	Status display
22260028	AB-B6-M8L-6-5,0PUR	-	5	6	With LEDs
22260029	AB-B6-M8L-6-10,0PUR	-	10	6	With LEDs
22260030	AB-B8-M8L-8-5,0PUR	-	5	8	With LEDs
22260031	AB-B8-M8L-8-10,0PUR	-	10	8	With LEDs
22260032	AB-B10-M8L-10-5,0PUR	-	5	10	With LEDs
22260033	AB-B10-M8L-10-10,0PUR	-	10	10	With LEDs
M12 connection				·	
22260038	AB-B4-M8L-4-M12	8	-	4	With LEDs
22260039	AB-B6-M8L-6-M12	8	-	6	With LEDs
M16 connection				·	· ·
22260034	AB-B4-M8L-4-M16	8	-	4	With LEDs
22260035	AB-B6-M8L-6-M16	10	-	6	With LEDs
22260036	AB-B8-M8L-8-M16	12	-	8	With LEDs
22260037	AB-B10-M8L-10-M16	14	-	10	With LEDs

**& LAPP** 

**Distribution Box M8**