

## EPIC® DATA M12X

Field mountable round cable coupler, IP67, IDC, qualified for 10 Gigabit

### Info

Cat.6<sub>A</sub> acc. to ISO/IEC 11801  
installation without tools



Supplementary automation components from Lapp



Mechanical and plant engineering



Assembly time



Interference signals

### Product features

Field assembly Industrial Ethernet connector  
Qualified for 10 Gigabit/s Ethernet  
Suitable for use in industrial applications  
Robust and vibrations- resistant  
Housing: zinc die-casting, grey  
Toolfree installation, small and compact design

### Norm references / Approvals

Cat.6<sub>A</sub> acc. to ISO/IEC 11801  
M12 X-coded acc. to IEC61076-2-109

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001121

ETIM 5.0 Class-Description: Modular connector

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001121

Last Update (10.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## EPIC® DATA M12X

Protection rating:	ETIM 6.0 Class-Description: Modular connector IP 67
Ambient temperature (operation):	-40°C to +85°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

## EPIC® DATA M12X

Article number	Article designation	Min. outer diameter (mm)	Max. outer diameter (mm)	Max. core diameter including insulation	AWG solid	AWG 7-wire
M12 X-coded plug, straight						
21700602	ED-IE-AX-M12X-6A-67-FC	6.3	9.7	1.6	26-22	26-22
M12 X-coded socket, straight						
21700621	ED-IE-AX-M12XF-6 <sub>A</sub> -67-FC	6.3	9.7	1.6	26-22	26-22
M12 X-coded socket, straight for wall mounting						
21700622	<sub>A</sub> -67-FC	6.3	9.7	1.6	26-22	26-22

Last Update (10.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03\_16