

CASPLAST™ UL/cUL

Style 1007

-20°C to +80°C, 300V



Construction

Type: electrical wire
Core: bare or tin-plated copper
Insulation: extruded PVC

Production

Range width: AWG 30 to 16
Options: consult us for any special requirements

Application

General use: internal cabling for electrical or electronic appliances, computers, etc.



General characteristics

Chemical behaviors: good resistance to aggressive chemical environments
Motion: good resistance to alternate bending

Thermal characteristics

Operating temperature: -20°C to +80°C

Electrical characteristics

Operating Voltage: 300V
Test voltage: 3000 V

Approvals – Standards

“Horizontal flame”: as per UL approval
UL approval: as per standard UL 758

Casmocable Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)
			(in)	(mm)						
11110401	16	26	0.010	0.254	0.059	1.5	0.016	0.4	0.091	2.3
11110402	18	16	0.010	0.254	0.046	1.17	0.016	0.4	0.077	1.95
		34	0.007	0.18	0.048	1.21	0.016	0.4	0.079	2
		41	0.006	0.16	0.046	1.18	0.016	0.4	0.078	1.98
		1	0.040	1.02	0.040	1.02	0.016	0.4	0.072	1.82
11110403	20	21	0.007	0.18	0.037	0.95	0.016	0.4	0.069	1.75
		1	0.032	0.813	0.032	0.813	0.016	0.4	0.063	1.6
		26	0.006	0.16	0.037	0.94	0.016	0.4	0.069	1.75
		10	0.010	0.254	0.037	0.93	0.016	0.4	0.069	1.75
		19	0.004	0.1	0.039	1	0.016	0.4	0.071	1.8
11110404	22	1	0.026	0.65	0.026	0.65	0.016	0.4	0.057	1.45
		7	0.010	0.254	0.030	0.77	0.016	0.4	0.061	1.56
		17	0.006	0.16	0.030	0.76	0.016	0.4	0.061	1.56
11110405	24	1	0.020	0.51	0.020	0.51	0.016	0.4	0.052	1.31
		7	0.008	0.2	0.024	0.61	0.016	0.4	0.056	1.41
		11	0.006	0.16	0.024	0.61	0.016	0.4	0.056	1.41
11110406	26	7	0.006	0.16	0.019	0.48	0.016	0.4	0.050	1.28
		1	0.016	0.4	0.016	0.4	0.016	0.4	0.047	1.2



COPYRIGHT

This document is protected under copyright law and is the property of Casmocable. Data contained herein is confidential to Casmocable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmocable or any affiliates without the prior written authorization of Casmocable.

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmocable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmocable is not responsible for any claim traceable to such error.

CASPLAST™ UL/cUL

Style 1007

-20°C to +80°C, 300V



Casmø Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)
			(in)	(mm)						
11110407	28	7	0.005	0.127	0.015	0.38	0.016	0.4	0.046	1.18
11110408	30	1	0.010	0.254	0.010	0.254	0.016	0.4	0.041	1.05
		7	0.004	0.1	0.012	0.3	0.016	0.4	0.043	1.1



COPYRIGHT

This document is protected under copyright law and is the property of Casmø Cable. Data contained herein is confidential to Casmø Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmø Cable or any affiliates without the prior written authorization of Casmø Cable.

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmø Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmø Cable is not responsible for any claim traceable to such error.